

Cu/HMWPE



Areas of Use

HMWPE cable is electrically connected (directly or indirectly) to the negative output terminal of a cathodic protection power supply. This includes bond cables to a cathodically protected structure. CP Cable is used as direct earth burial DC feeder cable in cathodic protection systems.

Cable Construction

Conductor	Stranded Annealed Copper (IEC/EN 60228, Class 2)
Insulation	High Molecular Weight Polyethylene (Black) Acc. to ASTM D1248 Type 3, Class C, Category 5, IEC 60502, ST7
Reference Standards	17-SAMSS-017

Technical Properties

Operating Voltage	0.6/1 kV
Test Voltage	3.5 kV
Temperature Range	Operation: -30°C...+90°C, Installation: -5°C...+70°C
Conductor Resistance	IEC/EN 60228
Min. Bending Radius	7.5 x Cable Diameter

Cross Section

Configuration / Cross-Section (mm/mm ²)	Cable Diameter (mm) (± 5%)	Copper Weight (kg / km)	~ Cable Weight (kg / km)
1 x 4*	8,10	35	85
1 x 6*	8,70	52	110
1 x 10*	9,40	93	155
1 x 16	10,30	140	230
1 x 25	11,60	225	310
1 x 35	12,60	310	400
1 x 50	14,30	415	530
1 x 70	16,60	606	745
1 x 95	17,8	820	1.005
1 x 120	20,50	1.060	1.290
1 x 150*	23,8	1.350	1590
1 x 185	24,40	1.640	1.905
1 x 240	26,50	2.100	2.390

27.06.2026 22:23

Legal Warning: The information in this catalog is for marketing purposes. 2M Kablo can change this catalog during product development and any

requirements. 2M Kablo can always change designs, technical specifications, images and other informations in this catalog without any notice. This catalog is only a guide and is valid at the time of download, not valid for an offer or contract.
If you need more information about the products in this catalog, please contact us via info@2mkablo.com or call +90 (212) 222 8250.