LIY(St)Y-TP

Areas of Use

These shielded and PVC insulated cables are used as signal transmission cables in industrial applications. These can be easily used with their flexible construction in narrow applications like electronic control systems of computer or audio systems or the communication sector, electronic circuits, measurement devices, machine design, office equipment, etc. These used for indoor applications. Screening protects the cable from the outer electrical effects.

Cable Construction

Conductor	Stranded Annealed Copper (IEC/EN 60228, Class 5, 0.34 mm²: Class 2)
Insulation	PVC (EN 50290-2-21)
Lay-up	Cores are twisted as pairs and pairs are stranded in layers
Separator	PET Foil
Drain Wire	Stranded Tinned Copper
Screen	Al-PET Foil
Outer Sheath	PVC (EN 50290-2-22), RAL 7001 - Grey
Reference Standards	VDE 0812, TS 13755
Core Colors	DIN 47100 or Black-White and Numbered

Technical Properties

Operating Voltage	0.14 mm²..0.25 mm² 250 V; 0.34 mm²..1.50 mm² 300 V / 500 V; 2.50 mm²..... 450 V / 750 V
Test Voltage	0.14 mm²..25 mm² 1200 V; 0.34 mm²..10 mm² 1500 V; 1.50 mm²..... 2500 V
Loop Resistance	0.14 mm²-≤276 Ω/km; 0.22 mm²-≤170 Ω/km; 0.25 mm²-≤155.6 Ω/km; 0.34 mm²-≤112 Ω/km; 0.50 mm²-≤78 Ω/km; 0.75 mm²-≤52 Ω/km; 1.00 mm²-≤39 Ω/km; 1.50 mm²-≤26.6 Ω/km
Insulation Resistance	>200 M.Ωxkm
Capacitance (@800Hz)	Core - Core: 0.14 mm²-≤80 nF/km; 0.22 mm²..0.34 mm²-≤100 nF/km; 0.50 mm²..0.75 mm²-≤110 nF/km; 1.00 mm²..1.50 mm²-≤120nF/km; 2.50 mm²- ≤140 nF/km Core-Screen: 0.14 mm²-≤120 nF/km; 0.22 mm²..0.34 mm²-≤150 nF/km; 0.50 mm²..0.75 mm²-≤170 nF/km; 1.00 mm²..1.50 mm²-≤180nF/km; 2.50 mm²- ≤240 nF/km
Indutance (approx.)	0.65 mH/km
Temperature Range	Fixed: -30 °C .....+70 °C, Flexible: -5 °C .....+70 °C
Flame Retardancy	IEC/EN 60332-1
Min. Bending Radius	Fixed: 8 x Cable Diameter, Flexible: 15 x Cable Diameter

09.11.2026 11:53

Legal Warning: The information in this catalog is for marketing purposes. 2M Kablo can change this catalog during product development and any requirements. 2M Kablo can always change designs, technical specifications, images and other informations in this catalog without any notice.This catalog is only a guide and is valid at the time of download, not valid for an offer or contract.
If you need more information about the products in this catalog, please contact us via info@2mkablo.com or call +90 (212) 222 8250.