HBH-K



Areas of Use

These indoor tinned telephone cables are used in the subscriber and switchboard system. These cables have halogen-free and flame retardant insulation and sheath.

Cable Construction

Conductor	Solid Tinned Copper (IEC/EN 60228)
Insulation	HFFR (EN 50290-2-26)
Core Colors	TSE K 116, IEC 60189-2
Lay-up	Pairs and bundles (each bundle contains of 10 pairs and identified by colored spiral tape)
Drain Core	Insulated Solid Annealed Copper (white color with red ring color)
Separator	PET Foil
Outer Sheath	HFFR (EN 50290-2-27), RAL 7032 - Grey
Reference Standards	TSE K 116, IEC 60189-2

Technical Properties

Operating Voltage	250 V
Test Voltage	1000 V
Conductor Resistance	≤97.8 Ω/km
Insulation Resistance	>100 M.Ωxkm
Mutual Capacitance	<120 nF/km
Capacitance Unbalance (800 Hz)	≤400 pF/500m
Temperature Range	-30 °C.....+70 °C
Flame Retardancy	IEC/EN 60332-1
Smoke Density	IEC/EN 61034-2
Amount of Halogen Acid Gas	IEC/EN 60754-1
Corrosive Gases Measurement	IEC/EN 60754-2
Min. Bending Radius (Fixed)	8 x Cable Diameter

14.09.2026 11:42

Legal Warning: The information in this catalog is for marketing purposes. 2M Kablo can change this catalog during product development and any requirements. 2M Kablo can always change designs, technical specifications, images and other informations in this catalog without any notice.This catalog is only a guide and is valid at the time of download, not valid for an offer or contract.
If you need more information about the products in this catalog, please contact us via info@2mkablo.com or call +90 (212) 222 8250.