


2XSLCH-JB



Areas of Use

Used in frequency converter controlled motors for control and/or power purposes, and suitable for use in dry, moist or wet environments in heavy industries. HFFR types are less flammable in case of fire, mostly self-extinguishing, have low smoke density and they do not emit poisonous and corrosive gasses during a fire.

Cable Construction

Conductor	Stranded Annealed Copper (IEC/EN 60228, Class 5)
Insulation	XLPE (Cross-Linked Polyethylene)
Core Colors	HD 308 S2
Lay-up	4 cores twisted together
Separator	Al-PET Foil
Screen	Tinned Copper Wire Braid
Outer Sheath	Halogen Free Flame Retardant Compound (HFFR/LSZH/LSOH/FRNC), RAL 9005 - Black
Reference Standards	Based on IEC 60502-1

Technical Properties

Operating Voltage	0.6/1 kV
Test Voltage	3.5 kV
Temperature Range	Operating: -30°C...+90°C, Installation: -10°C...+90°C
Smoke Density	IEC 61034-1/2
Corrosive Gases Measurement	IEC 60754-1/2
Min. Bending Radius	10 x Cable Diameter
Flame Retardancy	IEC 60332-1-2, IEC 60332-3-24
Conductor Resistance	IEC/EN 60228

28.08.2025 19:17

Legal Warning: The information in this catalog is for marketing purposes. 2M Kablo can change this catalog during product development and any requirements. 2M Kablo can always change designs, technical specifications, images and other informations in this catalog without any notice. This catalog is only a guide and is valid at the time of download, not valid for an offer or contract. If you need more information about the products in this catalog, please contact us via info@2mkablo.com or call +90 (212) 222 8250.