


2XSLCY-JB



Areas of Use

Used in frequency converter controlled motors for control and/or power purposes, and suitable for use in dry, moist or wet environments in heavy industries.

Cable Construction

Conductor	Stranded Annealed Copper (IEC/EN 60228, Class 5)
Insulation	XLPE (Cross-Linked Polyethylene)
Core Colors	HD 308 S2
Lay-up	4 cores twisted together
Separator	Al-PET Foil
Screen	Tinned Copper Wire Braid
Outer Sheath	PVC (Polyvinyl Chloride), RAL 9005 - Black (Transparent outer sheath is available upon request)
Reference Standards	Based on IEC 60502-1

Technical Properties

Operating Voltage	0.6/1 kV
Test Voltage	3 kV
Temperature Range	Operating: -30°C...+70°C, Installation: -5°C...+70°C
Min. Bending Radius	10 x Cable Diameter
Flame Retardancy	IEC 60332-1-2
Conductor Resistance	IEC/EN 60228

06.05.2026 1:22

Legal Warning: The information in this catalog is for marketing purposes. 2M Kablo can change this catalog during product development and any requirements. 2M Kablo can always change designs, technical specifications, images and other informations in this catalog without any notice. This catalog is only a guide and is valid at the time of download, not valid for an offer or contract.

If you need more information about the products in this catalog, please contact us via info@2mkablo.com or call +90 (212) 222 8250.